

**GAPVAX**  
**VHE SERIES**  
 HYDRO EXCAVATOR

GapVax custom builds to meet your needs.  
 Call today to discuss what best fits your business.  
 CNG and Single Axle options shown below.



**GAPVAX**  
**VHE SERIES**  
 HYDRO EXCAVATOR



AUTHORIZED GAPVAX DEALER:



HEADQUARTERS: 575 CENTRAL AVE.  
 JOHNSTOWN, PA 15902  
 888-442-7829

TEXAS OFFICE: 4510 UNDERWOOD RD.  
 LA PORTE, TX 77571  
 281-884-8648



WWW.GAPVAX.COM





# GAPVAX VHE SERIES

VACUUM HYDRO EXCAVATOR

Like all GapVax equipment, the VHE Series hydro excavator is built by the operator, for the operator, making it ideal for contractors and municipalities alike. Our full-length 6" subframe reinforces the chassis frame and provides a stable platform for the body while dumping. This industry-leading subframe reduces stress and minimizes flexing while operating the boom hose or driving the truck, allowing components to last longer and maintain performance over time. The full-opening tailgate, combined with a 50° dump angle, lets you get in and out of the dumpsite fast and efficiently. Built to perform. Designed to last. The GapVax VHE is Versatile, Reliable, and Durable.

## VACUUM SYSTEM:

- Positive displacement pump; 4,500 CFM, 18" Hg
- 500 HP transfer case with air-shift engagement
- Optional 4,000 CFM/27" Hg PD Blower

## 4,000 CFM, 27" HG PD BLOWER

## BOOM SYSTEM:

- 8" Telescoping boom with a 180° Rotation
- Standard 9' extension, 26' reach from center
- Heavy-duty dual lift cylinders
- Worm gear driven

## 8" TUBE IN TUBE BOOM

## FILTRATION:

- 10" Stainless steel floatball shutoff
- Centrifugal cyclone separator with full-opening door, 20" cleanout and removable vortex finder
- Washable, stainless steel vee wire screen (300 micron)
- Optional cartridge filtration for intermittent dry vac use

## MULTI-STAGE FILTRATION

## OTHER FEATURES INCLUDE:

- Mid-ship transfer case directs the power of the engine to the blower and hydraulic system
- Noise and vibration dampening mounts for blower
- Full-length 6" subframe to reinforce strength and allow for tube trays

## OPTIONS:

- Stainless steel debris body
- Heated cabinets for the water pump and hose reel
- Water heater 400,000 or 575,000 BTU
- Water recirculation system
- Pump-off systems
- Body Flush-out system
- Debris body vibrator
- Interior coating in the debris tank
- Boom remote lube manifold
- Various lighting options
- Storage options
- Wireless Remote/pendant

\*See our website for a complete listing



## 19 GPM; 2,900 PSI

### WATER SYSTEM:

- 6 gpm; 2,500 PSI
- 300-2,000 gallon water tank capacity
- Stainless steel water tank
- Shaft-driven Tri-plex water pump
- Optional water pump flow up to 40 GPM and PSI up to 5,800

## TOP LOADING BODY

### DEBRIS BODY:

- 4 to 15 cu. yd. debris body options
- Single axle configurations available
- 50° Dump angle for fast unloading and easy clean-out
- Full opening tailgate with field-adjustable locks that ensure a complete seal



\*SPECS SUBJECT TO CHANGE WITHOUT NOTICE

**VERSATILE.**

**RELIABLE.**

**DURABLE.**